

Electric Hinge



Model:

- ETH4W – 4 wire energy transfer hinge
- ETH8W – 8 wire energy transfer hinge

Features:

- UL Listing - 60LK - Flexible Connector on 4 wire model.
- High-temp Teflon wire used:
 - 4W – 26/19 gauge/strand wire – 1 amp. Continuous rating
 - 8W – 28/7 gauge/strand wire – 1 amp. Continuous rating
- Choose from Hager, Stanley, McKinney, PBB, Cal Royal and others.
- Five knuckle, three knuckle, two knuckle, swing clear, anchor and pivot hinges modified.
- Centered access holes on most five knuckle hinges make for an easier installation.
- 19 strand wire on 4 wire models assure long hinge life.
- 4' leads available
- 3 year warranty

Application:

The Energy Transfer Hinges series is ideal for doors that require concealed low voltage transfer of power from the door frame hinge jamb to the door.

Common applications include passing power to:

- Electrified locks
- Electrified exit device trim
- Electrified latch-retracting exit devices
- Any application where low voltage power must be transferred from the hinge jamb to the door.



ETH4W



ETH8W

Model:	Dimensions:	Finishes:
ETH4W	4 1/2" x 4"	US 26D
	4 1/2" x 4 1/2"	US 3, 4, 10, 10B, 26, 26D
ETH8W	4 1/2" x 4 1/2"	US 26D



Serving North America

Pennsylvania 800-233-4210 Fax: 800-854-4146	Missouri 800-211-4607 Fax: 800-211-4608	Nevada 800-722-4210 Fax: 800-248-3620	Texas 866-693-6903 Fax: 866-693-6904
--	--	--	---

www.topnotch.bz • sales@topnotch.bz

Notes:



Serving North America

Pennsylvania
800-233-4210
Fax: 800-854-4146

Missouri
800-211-4607
Fax: 800-211-4608

Nevada
800-722-4210
Fax: 800-248-3620

Texas
866-693-6903
Fax: 866-693-6904

www.topnotch.bz • sales@topnotch.bz