

# Full Mortise Bearing Hinges

# McKINNEY

## Standard Weight

### TA2714 STEEL BASE

### TA2314 STAINLESS STEEL, BRASS, OR BRONZE BASE

- Ball Bearing

Size (Inches)	Gauge	Size of Machine Screws	Size of Wood Screws	Available in NRP
3 1/2" x 3 1/2" *	.123	1/2" x 10-24	1" x 10	
4" x 4"	.130	1/2" x 12-24	1 1/4" x 12	•
4 1/2" x 4 1/2"	.134	1/2" x 12-24	1 1/4" x 12	•

\* Not available in stainless steel.

Finishes: US 3, 10, 10B, 26D, 32D, P.

### T2714 STEEL BASE

### T2314 STAINLESS STEEL, BRASS, OR BRONZE BASE

- Plain Bearing

Size (Inches)	Gauge	Size of Machine Screws	Size of Wood Screws	Available in NRP
3 1/2" x 3 1/2" *	.123	1/2" x 10-24	1" x 10	
4" x 4"	.130	1/2" x 12-24	1 1/4" x 12	
4 1/2" x 4 1/2"	.134	1/2" x 12-24	1 1/4" x 12	•

\* Not available in stainless steel.

Finishes: US 3, 10, 10A, 10B, 26, 26D, P.



Top Notch Distributors, Inc.

## Serving North America

**Pennsylvania**  
800-233-4210  
Fax: 800-854-4146

**Missouri**  
800-211-4607  
Fax: 800-211-4608

**Nevada**  
800-722-4210  
Fax: 800-248-3620

**Texas**  
866-693-6903  
Fax: 866-693-6904

[www.topnotch.bz](http://www.topnotch.bz) • [sales@topnotch.bz](mailto:sales@topnotch.bz)

# Full Mortise Concealed Bearing

# McKINNEY

## SPRING HINGE — ADJUSTABLE

### 1502 Steel Standard Weight

- For use on wood or metal doors in apartments, hotels, motels, office buildings and other public buildings.
- Two concealed nylon tee bearings for vertical and lateral loads. A dependable coil spring provides the closing power.
- Hinge has infinite adjustment, and tension can be added or reduced by means of a hex key, which is provided. Locking screw provides unparalleled tamper resistance after proper tension is set.
- Hinge fits regular gauge cutout and is standard template.
- Non-handed.

**CAUTION** — Use of gasket for smoke or sound protection, wind condition or unbalanced air pressure may prevent door from latching. Additional closing power would be required. NFPA requires a minimum of two (2) spring hinges on labeled doors.

Size (Inches)	Gauge	Size of Machine Screws	Size of Wood Screws
4" x 4" *	.130	1/2" x 12-24	1 1/4" x 12
4 1/2" x 4 1/2"	.134	1/2" x 12-24	1 1/4" x 12

\* Not available in stainless steel.

**Finishes: US 3, 4, 10, 15, 26, 26D, P.**



### Serving North America

**Pennsylvania**  
800-233-4210  
Fax: 800-854-4146

**Missouri**  
800-211-4607  
Fax: 800-211-4608

**Nevada**  
800-722-4210  
Fax: 800-248-3620

**Texas**  
866-693-6903  
Fax: 866-693-6904